

MACH

@MACH-WMS



WE MAKE SOLUTIONS



INDUSTRIA DE LA MADERA



LINEA COMPACT


línea de atención:

(57) 3227736734 / Bogotá Colombia




www.mach.com.co


COMPACT D



Encolado y Prensado



Retesteo de puntas




Refilado Superior/Inferior




Calderin
Intercambiable

Min. Panel Length	120mm
Min. Panel Width	80mm
Panel Thickness	10-45mm
Edgeband Width	12-48mm
Edgeband Thickness	0.4-3mm
Feeding Speed	8m/min
In-put voltage	380V Optional
In-put frequency	50Hz Optional
Total Power	4 kw
Air Pressure	0.5Mpa
Overall Dimension	1800mmx600mmx1410mm
Net Weight	500kg


COMPACT DSP




Rectificado (Tupi)




Encolado y Prensado



Retesteo de puntas



Refilado Superior/Inferior



Refiladores de Radio



Pulidores de Canto



Calderin
Intercambiable


Min. Panel Length	120mm
Min. Panel Width	80mm
Panel Thickness	10-45mm
Edgeband Width	12-48mm
Edgeband Thickness	0.4-3mm
Feeding Speed	8m/min
In-put voltage	380V Optional
In-put frequency	50Hz Optional
Total Power	5.86kw
Air Pressure	0.5Mpa
Overall Dimension	2580mmx600mmx1410mm
Net Weight	660kg

linea de atención:


(57) 3227736734 / Bogotá Colombia

www.mach.com.co


COMPACT DSA



Rectificado (Tupi)



Encolado y Prensado




Retesteo de puntas




Refilado Superior/Inferior



Rebordeador de Esquinas



Refiladores de Radio



Pulidores de Canto



Calderin
Intercambiable

Min. panel Length	100mm
Min. panel Width	45mm
Panel Thickness	10-45mm
Edge width	12-48mm
Edge thickness	0.4-3mm
Feeding Speed	8 -16m/min
In-put voltage	380V (optional)
In-put frequency	50Hz
Total Power	8.5kw
Air Pressure	0.6Mpa
Dimension	3950x780x1500mm
Net Weight	950kg



TT-10 PM



TT-30 PM



Model	TT-10PM	TT-20PM	TT-30PM
Working pressure	8 bar	8 bar	8 bar
Power	7.5Kw/10HP	15Kw/20HP	22Kw/30HP
Output air	1.06m ³ /min	2.2 m ³ /min	3.6 m ³ /min
Output pipe	G1/2	G3/4	G11/4
Cooling method	Air cooling	Air cooling	Air cooling
Driving mode	Direct drive	Direct drive	Direct drive
Start method	soft start	soft start	soft start
Voltage	380V, 50HZ	380V, 50HZ	380V, 50HZ
Overall dimensions(L*W*H)	800*600*845mm	1050*780*980mm	1200*880*1125mm
Net weight	140kg	260kg	360kg

TS-20 M

FOR LASER MACHINES



Model	TS-20PM
Working pressure	15 bar
Power	15Kw/20HP
Output air	1.2 m ³ /min
Output pipe	G3/4
Cooling method	Air cooling
Driving mode	Direct drive
Start method	soft start
Voltage	380V, 50HZ
Overall dimensions(L*W*H)	1700*750*1450mm
Net weight	400kg

línea de atención:

(57) 3227736734 / Bogotá Colombia

www.mach.com.co



PR3248

Model	CP3248X50
Table Size	2500x1250mm
MAX Pressure	50Ton(Adjustable)
Working Distance	1000mm
Cylinder	Φ125/Φ90x2pcs
Oil Pump	4Kw
Power	380V/50HZ
Package Size	2900x1250x2900mm
Net Weight	2000kg



PR3251



Model	CP32511X150
Table Size	3500x1500mm
MAX Pressure	150Ton(Adjustable)
Working Distance	1000mm
Cylinder	Φ125/Φ90x6pcs
Oil Pump	7.5Kw
Power	380V/50HZ
Package Size	3460x1500x2900mm
Net Weight	5900kg

línea de atención:

(57) 3227736734 / Bogotá Colombia

www.mach.com.co

**SECCIONADORAS
AUTOMATICAS/
SEMIAUTOMATICAS**

MACH
WMS

SIERRAS CNC



CE

Model	TT-280	TT-330
Max.Working width	2750mm	3250mm
Max.cutting thickness	100mm	100mm
Max.Working length	2600mm	3250mm
Sawing speed	0-80m/min	0-80m/min
main saw motor	15kw(optional)	15kw(optional)
Working air pressure	0.6Mpa	0.6Mpa
scoring saw motor	2.2kw	2.2kw
Total motor power	24kw	24kw
Overall dimensions(L*W*H)	5300*5450*1800mm	5900*6250*1800mm
Net weight	4800kg	5300kg



línea de atención:

(57) 3227736734 / Bogotá Colombia

www.mach.com.co

@MACH-WMS

MACH

@MACH-WMS



WE MAKE SOLUTIONS

COMPLEMENTARIOS



ROUTERS CNC

ESCUADRADORAS



EXTRACTORES



BISAGRADORES



REBORDEADORES



línea de atención:
(57) 3227736734 / Bogotá Colombia



SIGUENOS EN::

www.mach.com.co